



## VIZM.EX26616 Fittings, Rubber Gasketed

[Page Bottom](#)

### Fittings, Rubber Gasketed

[See General Information for Fittings, Rubber Gasketed](#)

**SHANDONG DINGLIANG FIRE TECHNOLOGY CO LTD**

EX26616

Cheliuzhuang Village Jiulong Sub-office Fangzi District  
Weifang, Shandong 261200 CHINA

#### Rigid Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT1	Rolled	10	1, 1-1/4, 1-1/2, 2, 3, 4, 5, 6, 8, 10	300
XGQT1	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 3, 4, 5, 6, 8, 10, 12	300
XGQT1	Cut, Rolled	GB/T3091	3 OD (76.1 mm), 5-1/2 OD (139.7 mm), 6-1/2 OD (165.1 mm)	300

#### Flexible Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT2	Rolled	10	1, 1-1/4, 1-1/2, 2, 3, 4, 5, 6, 8, 10	300
XGQT2	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 3, 4, 5, 6, 8, 10, 12	300
XGQT2	Cut, Rolled	GB/T3091	3 OD (76.1 mm), 5-1/2 OD (139.7 mm), 6-1/2 OD (165.1 mm)	300

#### Angle Pad Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT7	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10	300
XGQT7	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300
XGQT7	Rolled, Cut	T3091	3OD(76.1mm), 4-1/4OD(108.1mm), 5-1/4OD(133mm), 5-1/2OD(139.7mm), 6-1/4OD(159mm), 6-1/2OD(165.1mm);	300

#### Split Flange

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT5	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8, 10	300
XGQT5	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300
XGQT5	Cut, Rolled	GB/T3091	3 OD (76.1 mm), 5-1/2 OD (139.7 mm), 6-1/2 OD (165.1 mm)	300

#### Class 150 Split Flange

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT5A	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8, 10	300
XGQT5A	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300
XGQT5A	Rolled, Cut	T3091	3OD(76.1mm), 4-1/4OD(108.1mm), 5-1/4OD(133mm), 5-1/2OD(139.7mm), 6-1/4OD(159mm), 6-1/2OD(165.1mm);	300

#### Side Outlet/ Mechanical Tee

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT3G	Grooved	10, 40	2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2; 3 x 1, 1-1/4, 1-1/2, 2; 4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 OD (76.1 mm), 3; 6 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 4; 8 x 2-1/2, 3 OD (76.1 mm), 3, 4, 5-1/2OD(139.7mm), 6-1/2OD(165.1mm), 6;	300
XGQT3G	Grooved	GB/T3091	3 OD (76.1 mm) x 1; 5-1/2 OD (139.7 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4; 6-1/2 OD (165.1 mm) x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	300
XGQT3S	Threaded	10, 40	2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 3 x 1/2, 1, 1-1/4, 1-1/2; 4 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm); 6 x 1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3; 8 x 2, 3 OD (76.1 mm)	300
XGQT3S	Threaded	GB/T3091	3 OD (76.1 mm) x 1, 1-1/4, 1-1/2, 2; 6-1/2 OD (165.1 mm) x 1-1/4, 1-1/2, 2, 3 OD (76.1 mm)	300
XGQT3U	U-Type Threaded	10, 40	1 x 1/2, 3/4; 1-1/4 x 1/2, 3/4; 1-1/2 x 1/2, 3/4, 1; 2 x 1/2, 3/4, 1; 2-1/2 x 1/2, 3/4, 1	300
XGQT3U	U-Type Threaded	GB/T3091	3 OD (76.1 mm) x 1/2, 1	300

Models XGQT3S and XGQT3U in 1/2 in. (21 mm), 3/4 in. (26 mm) and 1 in nominal outlet sizes are intended for direct connection to sprinklers.

Models XGQT3G & XGQT3S in 1 in. (33.4 mm) and larger normal outlet sizes are intended for connection to system piping.

10 refers to Schedule 10 steel pipe in accordance with NFPA 13

40 refers to Schedule 40 steel pipe in accordance with NFPA 13

GB/T 3091 refers to steel pipe manufactured in accordance with GB/T 3091-2008



Trademark and/or Tradename:

Last Updated on 2016-07-06

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".